Innovation Pathway – EXPO & Networking" at Alcântara Green Roof WWRF

Advanced anaerobic digestion and co-digestion

Simon Christian SUEZ Water Technologies & Solutions

ready for the resource revolution





We have been *experts* in water and waste management for 160 years.

We operate on 5 continents, on which SUEZ harnesses all its desire for *innovation* to achieve an *efficient* and *sustainable management of resources* throughout the world.




full-service provider delivering across the value chain

solutions & services technologies delivery models Engineering, Procurement, 2 A Equipment Specialty chemicals Construction and systems and expert services Water quality Lifecycle services Build, Own & Operation monitoring Data intelligence Mobile **Operation & Maintenance** for asset performance Treatment




SUEZ WTS: project delivery across all AD sectors






4 WTS Anaerobic Digestion Technologies Portfolio - Biological Hydrolysis

SUEZ WTS: project delivery across all AD sectors






Solutions for Municipal Sludge Digestion




Integrating Biological Hydrolysis – Class A biosolids



Critical factor - All advanced digestion pre-treatment systems allow for significant increase in digester dry solids feed



Monsal 55






Biological Hydrolysis Operational Performance

Technology to Maximize Digester Efficiency


- Digester HRT: 13 to 18 Days
- Up to 3x's Effective Capacity (Gas production)
- OLR: > 4 kg VS/m³-day
- VS Reduction: ~ 55% @ 15d HRT
- Biogas Yield: > 400 m³/tonne dry solids
- Auto thermal with gas to CHP no additional thermal input required
- Reduced biosolids generation
- "Stabilised Biosolid" when needed



12 biological hydrolysis facilities installed globally



Continued performance Years after Commissioning






Biological Hydrolysis Operational Performance


Technology applications

- Only suitable for mixed sludge (50% primary)
- New built plants or retrofit to existing Sludge Treatment Centres
- Allows optimisation of digester asset
- Typically viable on plants
 +30TDS/day (Range 30 to +100TDS/day)
- Plant capacity expansion for additional sludge, co-digestion or co-location






Biogas Yield Efficiency (MWh electricity per tds / Digester HRT)





2 | Case studies and references





Case study 1: Avonmouth WWTW Whole facility optimisation



The challenge

- Phased development on a 1.1M
 PE WWTP
- Optimise digestion on existing infrastructure
- ✓ Increase digestion / reduce lime stabilisation of sludge
- ✓ Optimise utilisation of available CHP units (5.75MWe)
- Maintain operations during development
- Electricity generation for own use and export
- Enabler for commercial waste treatment activities




- Conventional Mesophilic Digestion
- ✓ 6 No 2,700m³ Digesters
- 22,000 tonnes dry solids per year to AD
- 21,097 tonnes dry solids per year to lime stabilisation




Avonmouth: Pre 2007


















Case study 2: Great Billing WWTW Centralisation of digestion



The challenge

- ✓ Optimise digestion on existing infrastructure ~20,000m³ digestion volume.
- Accommodate increased solids load from additional sludge imports for 1.6M PE WWTP
- ✓ Retain digesters
- Maintain operations during development
- ✓ Produce Class A biosolids
- ✓ Target energy export



Great Billing WWTW: Centralisation of digestion



40,000 TDS p.a. WWTW (~12,000 TDS indigenous, ~28,000 TDS imported) Solution as part of an integrated power and sludge upgrade 4 existing digesters retained 4.2MWe CHP capacity

VALUE PROPOSITION

- ✓ Optimization of existing digestion assets
- Increased sludge intake (imports from satellite centres)
- ✓ +ive thermal energy balance critical
- ✓ Class A product
- ✓ Low maintenance and intervention system
- ✓ Electricity output optimised

Great Billing WWTW: Centralisation of digestion





Monsal 55 EBH plant

Incorporating

- Monsal GasLift[™] System
- Monsal GasMix™
- Monsal Heating Equipment (HX and Steam)

SYSTEM PERFORMANCE

- ✓ 7.5% DS sludge
- ✓ Daily sludge flow of ~1,400cu.m/day
- ✓ Digester HRT 15days with additional digester
- ✓ VS conversion +55%



Hydrolysis plant reference list

Macclesfield BH

4,500 tds/annum, 6% BH feed, 2 day BH HRT, 17 day MAD HRT

Crewe BH

12,500 tds/annum, 6.5% BH feed, 2.1 day BH HRT, 16 day MAD HRT

Blackburn EBH

16,200 tds/annum, 6.0% EBH feed, 2.2 day EBH HRT, 12 day MAD HRT

Cambridge EBH

11,500 tds/annum, 4.5% EBH Feed, 2.1 day EBH HRT, 11.4 day MAD HRT

Avonmouth BH

30,700 tds/annum, 3 day BH HRT, 11 day MAD HRT

Kings Lynn EBH

19,200 tds/annum, 3 day EBH HRT, 15 day MAD HRT

Great Billing EBH


39,000 tds/annum, 7.5% EBH feed, 3.1 days EBH HRT, 11.3 days MAD HRT

Lancaster EBH

9,500 tds/annum, 5.2% EBH Feed, 3.0 days EBH HRT, 14.4 days MAD HRT

Trowbridge BH

10,950 tds/annum, 6% BH Feed, 2.0 days BH HRT, 14.0 days MAD HRT





Thank you for your attention

Simon Christian

Email:

Tel: +44 (0)7730 521677

